

MURATA CMCC products

For Power line - Automotive Grade -

(inch / mm)	2A	4A	6A	8A	10A	12A	14A	16A	18A	Rated Current		
4.0 × 4.0 × 1.5 max.mm (1515/4040)												
5.0 × 3.6 × 2.4 max.mm (2014/5036)	1.5 2.0 2.5 3.0 4.0										<p>Note: In regard to the rated current, derating may be necessary, depending on the operating temperature.</p>	
	1.5 2.0 2.5 3.0 4.0		▶ DLW5ATZ_MQ2 (-40 to +105°C)	▶ DLW5ATZ_TQ2 (-40 to +105°C)	▶ DLW5ATH_MQ2 (-40 to +125°C)	▶ DLW5ATH_TQ2 (-40 to +125°C)	▶ Infotainment	▶ Infotainment	▶ PowerTrain/Safety	▶ PowerTrain/Safety		
5.0 × 5.0 × 2.5 max.mm (2020/5050)	1.5 2.0 2.5 3.0 4.0											
	1.5 2.0 2.5 3.0 4.0		▶ DLW5BTZ_TQ2 (-40 to +105°C)	▶ DLW5BTH_TQ2 (-40 to +125°C)	▶ Infotainment	▶ PowerTrain/Safety						
5.0 × 5.0 × 4.5 max.mm (2020/5050)	0.7 1.0 1.5										▶ DLW5BSZ_TQ2 (-40 to +105°C)	▶ Infotainment
5.0 × 5.0 × 5.0 max.mm (2020/5050)	3.1 3.7 4.4 5.6										▶ PLT5BPH (-55 to +150°C)	▶ PowerTrain/Safety
9.0 × 7.0 × 5.0 max.mm (3527/9070)			5.0								▶ UCMH90-0001 (-40 to +150°C)	▶ PowerTrain/Safety
12.9 × 6.6 × 9.3 max.mm	▶ PLT10HH (-55 to +105°C)		6.0 10.0								▶ PowerTrain/Safety	
	▶ PLT10HH (-55 to +125°C)		6.0 10.0		15.0 18.0						▶ PowerTrain/Safety	
	▶ PLT10HH (-55 to +150°C)		6.0 10.0		15.0						▶ PowerTrain/Safety	